



**NAFL2**  
Eccentric locking collar type

Unit No.	Shaft Dia.		Dimensions (mm)										Bolt Size	Bearing No.	Housing No.	Mass (kg)	Available N
	d (in.)	d (mm)	H	J	L	A <sub>2</sub>	A <sub>1</sub>	A	E	N	S						
NAFL202 202-10 203 203-11	5/8 11/16	15 17	99	76.5	57	15	11	25.5	38.4	11.5	13.9	M10	NA202 202-10 203 203-11	FL203	0.48	--	
NAFL204-12 204	3/4	20	113	90	60	15	11	25.5	41.5	11.5	17	M10	NA204-12 204	FL204	0.7	12	
NAFL205-14 205-15 205 205-16	7/8 15/16 1	25	130	99	68	16	13	27	42.9	11.5	17.4	M10	NA205-14 205-15 205 205-16	FL205	0.8	16	
NAFL206-18 206 206-19 206-20	1-1/8 1-3/16 1-1/4	30	148	117	80	18	13	31	48.1	11.5	18.2	M10	NA206-18 206 206-19 206-20	FL206	1.2	16	
NAFL207-20 207-21 207-22 207 207-23	1-1/4 1-5/16 1-3/8 1-7/16	35	161	130	90	19	14	34	51.3	14	18.8	M12	NA207-20 207-21 207-22 207 207-23	FL207	1.6	16	
NAFL208-24 208-25 208	1-1/2 1-9/16	40	175	144	100	21	14	36	55.9	14	21.4	M12	NA208-24 208-25 208	FL208	1.9	16	
NAFL209-26 209-27 209-28 209	1-5/8 1-11/16 1-3/4	45	188	148	108	22	16	38	56.9	18	21.4	M16	NA209-26 209-27 209-28 209	FL209	2.3	19	
NAFL210-30 210-31 210	1-7/8 1-15/16	50	197	157	115	22	16	40	60.1	18	24.6	M16	NA210-30 210-31 210	FL210	2.6	19	
NAFL211-32 211-34 211 211-35	2 2-1/8 2-3/16	55	224	184	130	25	18	43	68.6	18	27.7	M16	NA211-32 211-34 211 211-35	FL211	3.8	19	
NAFL212-36 212 212-38 212-39	2-1/4 2-3/8 2-7/16	60	250	202	140	29	18	48	75.8	18	30.9	M16	NA212-36 212 212-38 212-39	FL212	4.8	23	
NAFL213-40 213	2-1/2	65	258	210	155	30	20	50	81.6	23	34.1	M20	NA213-40 213	FL213	6.0	--	
NAFL214-44 214	2-3/4	70	265	216	160	31	20	54	82.6	23	34.1	M20	NA214-44 214	FL214	6.3	--	
NAFL215 215-48	3	75	275	225	164	34	22	55	88.8	23	37.3	M20	NA215 215-48	FL215	7.2	--	
NAFL216		80	290	233	180	34	22	58	91.9	25	37.3	M22	NA216	FL216	7.37	--	