



NAFLU2
Eccentric locking collar type

Unit No.	Shaft Dia.		Dimensions (mm)										Bolt Size	Bearing No.	Housing No.	Mass (kg)	
	d		H	J	L	A ₂	A ₁	A	E	N	S						
	(in.)	(mm)															
NAFLU202 202-10	5/8	15															
NAFLU203 203-11	11/16	17	99	76.5	57	15	11	25.5	38.4	11.5	13.9	M10	NA202 202-10 NA203 203-11	FLU203	0.64		
NAFLU204-12 204	3/4	20	112.5	90	61	19	15	29.5	45.5	11.5	17	M10	NA204-12 204	FLU204	0.7		
NAFLU205-14 205-15 205 205-16	7/8 15/16 1	25	123	99	70	19	15	30	45.9	11.5	17.4	M10	NA205-14 205-15 205 205-16	FLU205	0.8		
NAFLU206-18 206 206-19 206-20	1-1/8 1-3/16 1-1/4	30	142	116.5	82	20	16	32.5	50.1	11.5	18.2	M10	NA206-18 206 206-19 206-20	FLU206	1.2		
NAFLU207-20 207-21 207-22 207 207-23	1-1/4 1-5/16 1-3/8 1-7/16	35	158	130	94	21	17	36	53.3	14	18.8	M12	NA207-20 207-21 207-22 207 207-23	FLU207	1.6		
NAFLU208-24 208-25 208	1-1/2 1-9/16	40	172	143.5	103	24	17	39	58.9	14	21.4	M12	NA208-24 208-25 208	FLU208	1.9		
NAFLU209-26 209-27 209-28 209	1-5/8 1-11/16 1-3/4	45	180	148.5	108	24	18	40	58.9	16	21.4	M14	NA209-26 209-27 209-28 209	FLU209	2.3		
NAFLU210-30 210-31 210 210-32	1-7/8 1-15/16 2	50	190	157	114	28	20	45	66.1	18	24.6	M16	NA210-30 210-31 210 210-32	FLU210	2.6		
NAFLU211-32 211-34 211 211-35	2 2-1/8 2-3/16	55	217	184	128	31	21	48	74.6	18	27.7	M16	NA211-32 211-34 211 211-35	FLU211	3.8		
NAFLU212-36 212 212-38 212-39	2-1/4 2-3/8 2-7/16	60	237	202	138	34	21	53	80.8	18	30.9	M16	NA212-36 212 212-38 212-39	FLU212	4.8		
NAFLU213-40 213	2-1/2	65	256	210	152	38	22	56	89.6	21	34.1	M18	NA213-40 213	FLU213	6.0		
NAFLU214-44 214	2-3/4	70	264	216	157	38	23	58	89.6	21	34.1	M18	NA214-44 214	FLU214	6.3		
NAFLU215-47 215 215-48	2-15/16 3	75	275	225	164	41	24	62	95.8	21	37.3	M18	NA215-47 215 215-48	FLU215	7.2		