



**NAFL3**  
Eccentric locking collar type

Unit No.	Shaft Dia.		Dimensions (mm)									Bolt Size	Bearing No.	Housing No.	Mass (kg)
	d (in.)	(mm)	H	J	L	A <sub>2</sub>	A <sub>1</sub>	A	E	N	S				
NAFL305-14 305-15 305 305-16	7/8 15/16 1	25	150	113	80	16	13	29	46.1	19	16.7	M16	NA305-14 305-15 305 305-16	FL305	1.1
NAFL306-18 306 306-19	1- 1/8 1- 3/16	30	180	134	90	18	15	32	50.5	23	17.5	M20	NA306-18 306 306-19	FL306	1.6
NAFL307-20 307-21 307-22 307 307-23	1- 1/4 1- 5/16 1- 3/8 1- 7/16	35	185	141	100	20	16	36	53.3	23	18.3	M20	NA307-20 307-21 307-22 307 307-23	FL307	2.0
NAFL308-24 308-25 308	1- 1/2 1- 9/16	40	200	158	112	23	17	40	60.3	23	19.8	M20	NA308-24 308-25 308	FL308	2.6
NAFL309-26 309-27 309-28 309	1- 5/8 1-11/16 1- 3/4	45	230	177	125	25	18	44	63.9	25	19.8	M22	NA309-26 309-27 309-28 309	FL309	3.6
NAFL310-30 310-31 310	1- 7/8 1-15/16	50	240	187	140	28	19	48	70	25	24.6	M22	NA310-30 310-31 310	FL310	4.6
NAFL311-32 311-34 311 311-35	2 2-1/8 2-3/16	55	250	198	150	30	20	52	75.2	25	27.8	M22	NA311-32 311-34 311 311-35	FL311	5.3
NAFL312-36 312 312-38 312-39	2-1/4 2-3/8 2-7/16	60	270	212	160	33	22	56	80	31	29.5	M27	NA312-36 312 312-38 312-39	FL312	6.4
NAFL313-40 313	2- 1/2	65	295	240	175	33	25	58	86.2	31	32.5	M27	NA313-40 313	FL313	8.2