



SBLF2G
Setscrew Type

SALF2G
Eccentric Locking Collar Type

| Unit No. | Shaft Dia. | | Dimensions (mm) | | | | | | | | | Bolt Size | | Bearing No. | Housing No. | Mass (kg) |
|--|------------|-----------|-----------------|------|----|----------------|------|----------------|----|-----|------|-----------|------|--|-------------|----------------------|
| | d (in.) | d (mm) | H | J | L | A ₁ | A | A ₂ | N | S | E | | | | | |
| SBLF201G 201-8G 202G 202-10G 203G 203-11G | 1/2 | 12 | 81 | 63.5 | 56 | 9.5 | 18 | 9.5 | 8 | 6 | 25.5 | M6 | 1/4 | SB201G 201-8G 202G 202-10G 203G 203-11G | LF203 | 0.27 0.26 0.25 |
| | 5/8 | 15 | | | | | | | | | | | | | | |
| | 11/16 | 17 | | | | | | | | | | | | | | |
| | 3/4 | 20 | | | | | | | | | | | | | | |
| SBLF204-12G 204G | 3/4 | 20 | 90 | 71.5 | 61 | 11 | 20 | 11 | 10 | 7 | 29 | M8 | 5/16 | SB204-12G 204G | LF204 | 0.33 |
| SBLF205-14G 205-15G 205G 205-16G | 7/8 | 25 | 95 | 76 | 64 | 11 | 20 | 11 | 10 | 7.5 | 30.5 | M8 | 5/16 | SB205-14G 205-15G 205G 205-16G | LF205 | 0.38 |
| | 15/16 | | | | | | | | | | | | | | | |
| SBLF206-18G 206G 206-19G 206-20G | 1-1/8 | 30 | 113 | 90.5 | 76 | 12 | 22.5 | 12 | 12 | 8 | 34 | M10 | 3/8 | SB206-18G 206G 206-19G 206-20G | LF206 | 0.56 |
| | 1-3/16 | | | | | | | | | | | | | | | |
| | 1-1/4 | | | | | | | | | | | | | | | |
| SBLF207-20G 207-21G 207-22G 207G 207-23G | 1-1/4 | 35 | 122 | 100 | 89 | 13 | 24 | 13 | 12 | 9 | 36.5 | M10 | 3/8 | SB207-20G 207-21G 207-22G 207G 207-23G | LF207 | 0.80 |
| | 1-5/16 | | | | | | | | | | | | | | | |
| | 1-3/8 | | | | | | | | | | | | | | | |
| | 1-7/16 | | | | | | | | | | | | | | | |

| Unit No. | Shaft Dia. | | Dimensions (mm) | | | | | | | | | Bolt Size | | Bearing No. | Housing No. | Mass (kg) |
|--|------------|-----------|-----------------|------|----|----------------|------|----------------|----|-----|------|-----------|------|--|-------------|---------------------|
| | d (in.) | d (mm) | H | J | L | A ₁ | A | A ₂ | N | S | E | | | | | |
| SALF201G 201-8G 202G 202-10G 203G 203-11G | 1/2 | 12 | 81 | 63.5 | 56 | 9.5 | 18 | 9.5 | 8 | 6.5 | 32 | M6 | 1/4 | SA201G 201-8G 202G 202-10G 203G 203-11G | LF203 | 0.3 0.29 0.28 |
| | 5/8 | 15 | | | | | | | | | | | | | | |
| | 11/16 | 17 | | | | | | | | | | | | | | |
| | 3/4 | 20 | | | | | | | | | | | | | | |
| SALF204-12G 204G | 3/4 | 20 | 90 | 71.5 | 61 | 11 | 20 | 11 | 10 | 7 | 33.5 | M8 | 5/16 | SA204-12G 204G | LF204 | 0.33 |
| SALF205-14G 205-15G 205G 205-16G | 7/8 | 25 | 95 | 76 | 64 | 11 | 20 | 11 | 10 | 7.5 | 34 | M8 | 5/16 | SA205-14G 205-15G 205G 205-16G | LF205 | 0.42 |
| | 15/16 | | | | | | | | | | | | | | | |
| SALF206-18G 206G 206-19G 206-20G | 1-1/8 | 30 | 113 | 90.5 | 76 | 12 | 22.5 | 12 | 12 | 8 | 37.9 | M10 | 3/8 | SA206-18G 206G 206-19G 206-20G | LF206 | 0.60 |
| | 1-3/16 | | | | | | | | | | | | | | | |
| | 1-1/4 | | | | | | | | | | | | | | | |
| SALF207-20G 207-21G 207-22G 207G 207-23G | 1-1/4 | 35 | 122 | 100 | 89 | 13 | 24 | 13 | 12 | 9 | 41 | M10 | 3/8 | SA207-20G 207-21G 207-22G 207G 207-23G | LF207 | 0.85 |
| | 1-5/16 | | | | | | | | | | | | | | | |
| | 1-3/8 | | | | | | | | | | | | | | | |
| | 1-7/16 | | | | | | | | | | | | | | | |

Remarks: These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "G".