



**SBFD2G**  
Setscrew Type

**SAFD2G**  
Eccentric Locking Collar Type

Unit No.	Shaft Dia.		Dimensions (mm)									Bolt Size		Bearing No.	Housing No.	Mass (kg)
	d		H	J	L	A	A <sub>2</sub>	N	S	E						
	(in.)	(mm)														
SBFD204-12G 204G	3/4	20	90	71	67	17	9.5	10	7	27.5	M8	5/16	SB204-12G 204G	FD204	0.4	
SBFD205-14G 205-15G 205G 205-16G	7/8 15/16 1	25	95.2	76.2	71	17.5	9.5	10	7.5	29	M8	5/16	SB205-14G 205-15G 205G 205-16G	FD205	0.5	
SBFD206-18G 206G 206-19G 206-20G	1-1/8 1-3/16 1-1/4	30	113	90.5	84	21	12	12	8	33	M10	3/8	SB206-18G 206G 206-19G 206-20G	FD206	0.8	
SBFD207-20G 207-21G 207-22G 207G 207-23G	1-1/4 1-5/16 1-3/8 1-7/16	35	125	100	94	22	12.5	12	9	35.5	M10	3/8	SB207-20G 207-21G 207-22G 207G 207-23G	FD207	0.9	

Unit No.	Shaft Dia.		Dimensions (mm)									Bolt Size		Bearing No.	Housing No.	Mass (kg)
	d		H	J	L	A	A <sub>2</sub>	N	S	E						
	(in.)	(mm)														
SAFD204-12G 204G	3/4	20	90	71	67	17	9.5	10	7	32	M8	5/16	SA204-12G 204G	FD204	0.5	
SAFD205-14G 205-15G 205G 205-16G	7/8 15/16 1	25	95.2	76.2	71	17.5	9.5	10	7.5	32.5	M8	5/16	SA205-14G 205-15G 205G 205-16G	FD205	0.5	
SAFD206-18G 206G 206-19G 206-20G	1-1/8 1-3/16 1-1/4	30	113	90.5	84	21	12	12	8	37.9	M10	3/8	SA206-18G 206G 206-19G 206-20G	FD206	0.8	
SAFD207-20G 207-21G 207-22G 207G 207-23G	1-1/4 1-5/16 1-3/8 1-7/16	35	125	100	94	22	12.5	12	9	41	M10	3/8	SA207-20G 207-21G 207-22G 207G 207-23G	FD207	1.0	

Remarks: These numbers indicate relubricatable type. If maintenance free type is needed, please order without suffix "G".